

PTO

Please type a plus sign (+) inside this box →

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
collection of information unless it displays a valid OMB control number.

UTILITY
PATENT APPLICATION
TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.	KCX-197 (14737)
---------------------	-----------------

First Inventor or Application Identifier	Varriale et al
--	----------------

Title	Method and Apparatus for Multistage .
-------	---------------------------------------

Express Mail Label No.	ET891585920US
------------------------	---------------

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 27]
(preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawings (35 U.S.C. 113) [Total Sheets 2]
4. Oath or Declaration [Total Pages 1]
- a. ☐ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.61 (for continuation/divisional with Box 16 completed))
- i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application see 37 C.F.R. §§ 1.63(d)(2) and 1.133(c)

5. ☐ Microfiche Computer Program (*Appendix*)
6. Nucleotide and/or Amino Acid Sequence Submission (*if applicable, all necessary*)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ Small Entity Statement(s) ☐ Statement filed in prior application,
(PTO/SB/03-12) Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)
(If foreign priority is claimed)
15. ☒ Other: Express Mail Certificate

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

Prior application information: Examiner

Group / Act / Unit:

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

- ☐
- Customer Number or Bar Code Label


(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

Name	Neil C. Jones
	Nelson Mullins Riley & Scarborough

Address	Keenan Building, Third Floor
	1330 Lady Street

City	Columbia	State	SC	Zip Code	29201
Country	US	Telephone	864-250-2260	Fax	864-250-2394

Name (Print/Type)	Neil C. Jones	Registration No. (Attorney/Agent)	35,561
Signature		Date	9/28/00

Burden Hour Statement: This form is estimated to take 0.5 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

FEE TRANSMITTAL for FY 2000

Patent fees are subject to annual revision.

Small Entity payments must be supported by a small entity statement, otherwise large entity fees must be paid. See Forms PTO/SB/09-12. See 37 C.F.R. §§ 1.27 and 1.28.

TOTAL AMOUNT OF PAYMENT (\$) 1,176

Complete if Known

Application Number Not yet assigned
Filing Date Herewith
First Named Inventor Varriale et al.
Examiner Name Unknown
Group / Art Unit 1731
Attorney Docket No. KCX-197 (14737)

METHOD OF PAYMENT (check one)

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:

Deposit Account Number 50-1196
Deposit Account Name Nelson Mullins Riley...

☒ Charge Any Additional Fee Required Under 37 CFR §§ 1.16 and 1.17

2. ☒ Payment Enclosed:

☒ Check ☐ Money Order ☐ Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity Small Entity	Fee Code (\$)	Fee Code (\$)	Fee Description	Fee Paid
101 690 201 345			Utility filing fee	690
106 310 206 155			Design filing fee	
107 480 207 240			Plant filing fee	
108 690 208 345			Reissue filing fee	
114 150 214 75			Provisional filing fee	

SUBTOTAL (1) (\$) 690

2. EXTRA CLAIM FEES

Total Claims	Extra Claims	Fee from below	Fee Paid
47	27	18	486
3	0	78	0
Multiple Dependent		260	0

**or number previously paid, if greater; For Reissues, see below

Large Entity Small Entity	Fee Code (\$)	Fee Code (\$)	Fee Description	Fee Paid
103 18 203 9			Claims in excess of 20	
102 78 202 39			Independent claims in excess of 3	
104 260 204 130			Multiple dependent claim, if not paid	
109 78 209 39			** Reissue independent claims over original patent	
110 18 210 9			** Reissue claims in excess of 20 and over original patent	

SUBTOTAL (2) (\$) 486

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Small Entity	Fee Code (\$)	Fee Code (\$)	Fee Description	Fee Paid
105 130 205 65			Surcharge - late filing fee or oath	
127 50 227 25			Surcharge - late provisional filing fee or cover sheet	
139 130 139 130			Non-English specification	
147 2,520 147 2,520			For filing a request for reexamination	
112 920* 112 920*			Requesting publication of SIR prior to Examiner action	
113 1,840* 113 1,840*			Requesting publication of SIR after Examiner action	
115 110 215 55			Extension for reply within first month	
116 380 216 190			Extension for reply within second month	
117 870 217 435			Extension for reply within third month	
118 1,360 218 680			Extension for reply within fourth month	
128 1,650 228 925			Extension for reply within fifth month	
119 300 219 150			Notice of Appeal	
120 300 220 150			Filing a brief in support of an appeal	
121 260 221 130			Request for oral hearing	
138 1,510 138 1,510			Petition to institute a public use proceeding	
140 110 240 55			Petition to revive - unavoidable	
141 1,210 241 605			Petition to revive - unintentional	
142 1,210 242 605			Utility issue fee (or reissue)	
143 430 243 215			Design issue fee	
144 580 244 290			Plant issue fee	
122 130 122 130			Petitions to the Commissioner	
123 50 123 50			Petitions related to provisional applications	
126 240 126 240			Submission of Information Disclosure Stmt	
581 40 581 40			Recording each patent assignment per property (lines number of properties)	
146 690 246 345			Filing a submission after final rejection (37 CFR § 1.129(a))	
149 690 249 345			For each additional invention to be examined (37 CFR § 1.129(b))	

Other fee (specify) _____

Other fee (specify) _____

* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) 0

SUBMITTED BY

Name (Print/Type) Neil G. Jones

Signature

Registration No. (Attorney/Agent) 35,561

Complete (if applicable)

Telephone 864-250-2260

Date 9/28/00

WARNING:

Information on this form may become public. Credit card information should be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20331. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20331.

LAW OFFICES
NELSON MULLINS RILEY & SCARBOROUGH, L.L.P.

A REGISTERED LIMITED LIABILITY PARTNERSHIP

NEIL C. JONES
REGISTERED PATENT ATTORNEY
(864) 250-2200
INTERNET ADDRESS: NCJ@NMRS.COM

POINSETT PLAZA
104 SOUTH MAIN STREET, SUITE 900
POST OFFICE BOX 10084
GREENVILLE, SOUTH CAROLINA 29601

TELEPHONE (864) 250-2300
FACSIMILE (864) 232-2925
DIRECT FACSIMILE (864) 250-2394
WWW.NMRS.COM

OTHER OFFICES:
ATLANTA, GEORGIA
CHARLESTON, SOUTH CAROLINA
CHARLOTTE, NORTH CAROLINA
COLUMBIA, SOUTH CAROLINA
MYRTLE BEACH, SOUTH CAROLINA
MUNICH, GERMANY

10-25 U.S. PTO
09/575464
09/28/00

Express Mail Certificate

Applicant: Kimberly-Clark Worldwide, Inc.
Serial Number: Not yet assigned
Filed: Herewith
Title: Method and Apparatus for Multistage Liquid Filtration
Our Reference: KCX-197 (14747)
03768/9376

Express Mail Label Number: EJ891585920US
Date of Deposit: September 28, 2000

I hereby certify that this paper, all attachments, and any fees are being deposited with the U.S. Postal Service as "Express Mail" on the date indicated above and is addressed: Box Patent Application, Assistant Commissioner of Patents, Washington, DC 20231.

Diane Filatov

(Typed or printed name of person mailing paper or fee)

Diane Filatov

(Signature of person mailing paper or fee)

DOCKET NO: KCX-197-198 (14735/14737)
03768/9376

UNITED STATES PROVISIONAL PATENT APPLICATION

OF

MONICA G. VARRIALE

ROBERT J. LYNQ

AND

MICHAEL S. BRUNNER

FOR

METHOD AND APPARATUS FOR MULTISTAGE
LIQUID FILTRATION

**METHOD AND APPARATUS FOR MULTISTAGE
LIQUID FILTRATION**

The present invention is based on provisional patent application Serial Number 60/156,892 filed September 30, 1999, and
5 priority is hereby claimed therefrom.

Field of the Invention

The present invention relates to an apparatus and process for the removal of undesired particulates and microorganisms from water and other liquids. More particularly, the present invention relates to
10 an apparatus and process for the more efficient filtration of liquids such as water.

Background of the Invention

Water intended for human consumption is expected to be either free of harmful constituents or contain concentrations of such
15 constituents that are below harmful levels. To provide potable water for use in homes and businesses, municipalities utilize industrial scale processes in an effort to eliminate or reduce harmful constituents present in water drawn from large, naturally occurring water sources. Potable water is also frequently obtained on a
20 smaller scale from wells and springs and usually without any treatment prior to consumption.

Unfortunately, the potability of a particular water supply is sometimes questionable. The consistency and efficiency of treatment by municipalities may vary due to numerous factors such
25 as heavy rainfall, equipment failures, and usage levels. Depending upon the seriousness of a variation in treatment, a municipality may be forced to notify its consumers that further treatment of the water supplied, e.g. boiling, is required at the point of use before consumption is safe. Water obtained directly from a natural source

may also become suspect depending upon environmental conditions near the source. For examples, wells and springs can be contaminated due to rain water run-off washing a contaminant into the source. Accordingly, a need exists for liquid filtration devices suitable in size and scale for residential or office use.

In response, liquid filtration devices have been developed. Such devices range from those located at the point-of-use (e.g. the spigot of a kitchen sink, gravity-flow dispensers such as water pitchers, and low-pressure dispensers such as sports bottles) to the generally bulkier point-of-entry units hidden from view within the plumbing of a home or office. Many of these devices use activated charcoal in at least one stage of the filtration process. Activated charcoal helps to remove strong odors and tastes from water. More specifically, activated charcoal can remove chlorine, and sediment from water.

A problem associated with the use of activated charcoal (also referred to as activated carbon) is that certain microorganisms, like bacteria, propagate rapidly within activated charcoal. This problem has at least three undesirable effects. First, the growth of bacteria within the charcoal may inhibit the flow of water through this stage of the filter. Second, and more importantly, the use of activated charcoal can actually increase the concentration of bacteria present in the water by providing a moist, nutrient-rich environment that is conducive to bacterial reproduction as described in Daschner et al., Microbiological Contamination of Drinking Water in a Commercial Household Water Filter System, 15 Eur. J. Clin. Microbiol. Infect. Dis. 233-37 (1996). Third, for those uses that are intermittent, the first flow of water through the activated charcoal after a period of nonuse will contain a spike concentration of bacteria.

Typically, a certain concentration of bacteria is present in all water supplies. This concentration can increase in activated charcoal that is not flushed by the periodic use of water from a particular filter. The result is a spike concentration present in each intermittent use as the bacteria is flushed from the activated charcoal. Increased bacteria concentration is the opposite result intended by the filter installation. While many filtration mechanisms are available, none address all of these challenging problems without frequent replacement of the activated charcoal.

U.S. Patent No. 5,271,837 describes a multistage system for the filtration of drinking water utilizing a central filter cartridge constructed of activated charcoal impregnated with silver, a cation exchange resin, and an anion exchange resin. The activated charcoal is the first stage of the filtration system, followed by the resins. To prevent particulates from clogging the central filter cartridge, U.S. Patent No. 5,271,837 discloses a particulate filter located prior to the central filter cartridge. This patent, however, does not address any problems unique to the filtration of microorganisms or the prevention of bacteria growth on the activated charcoal.

U.S. Patent No. 5,891,333 describes a modular, multistage water filter for use in countertop or below-countertop applications. This patent is directed to a device with removable, replaceable cartridges containing filter media within a configuration that permits changes in size scale depending upon the filtration capacity desired.

The disclosure does not specify any particular filter media or constituent filtration sequence. The removal of any particular constituent from a water supply is not taught.

U.S. Patent No. 5,318,703 describes a water filter module for

use in coffee brewing that is designed to remove residual chlorine, odors, foul tastes, impurities, and unspecified other sediments from water prior to contact with the coffee grinds. The filter media disclosed is activated carbon which is held in place by mesh screens.

5 The mesh screens, which may be a polymer material, are included to remove large particulate impurities, such as sediment and other dirt particles, by mechanical filtration. The removal of microorganisms or any specific problems associated therewith is not addressed.

10 A disposable filter constructed of a paper filter media is presented in U.S. Patent No. 5,554,288. Finely-divided adsorbents are uniformly distributed throughout a pulp from which a paper filter media is created for use in variety of configurations. Various adsorbents are claimed, including activated carbon. U.S. Patent No.
15 5,554,288 specifically recognizes that carbon filter cartridges that remain immersed in the water being treated may become a hospitable medium for bacteria growth. However, as claimed, this particular problem is avoided because the filters of U.S. Patent No. 5,554,288 are discarded after use rather than remaining immersed in
20 the water. This solution, however, requires the user to frequently replace the filter, and requires disposal of the spent filter.

Therefore, a need has existed for an improved method and apparatus for the removal of undesired particulates and microorganisms, such as bacteria, viruses, protozoans, yeast, fungi,
25 and microbiological cysts, from liquids such as water. More particularly, a need for an improved method and apparatus for the filtration of liquids with greater filtration efficiency and the elimination of spike concentrations of microorganisms has existed that is not addressed by the prior art.

Summary of the Invention

The present invention addresses some of the problems identified above by providing a method and apparatus for filtering fluids such as water that reduces bacteria contact with the activated charcoal stage of the filter. More specifically, a filter stage is placed in the water stream of a multistage filter at a point in flow prior to the activated carbon such that the microorganisms are substantially removed from the water prior to the filtration by the activated carbon.

By consequently preventing bacteria contact with the activated charcoal, the problems of increased bacteria concentration and associated flow reduction are avoided. For uses that are intermittent, the problem of spike concentrations is avoided by preventing the microorganisms from reaching the activated carbon where conditions for reproduction may be conducive during periods of no water flow.

Multiple embodiments of the invention may be employed. For example, the filter may consist of stages in the form of beds of material in a stacked configuration within a cylindrically- or otherwise-shaped chamber. The liquid may enter the chamber from one end, pass longitudinally through the various stages of filter media, and then exit the chamber to a point of use. Other configurations of the filter system are also within the scope of the present invention and modifications to the structural configurations should not affect the ability of the presently-inventive apparatus and process to effectively filter fluids such as water. It should be understood that while a water filtering process is exemplified herein, the present process and apparatus may be utilized for filtering other liquids depending on the contaminant removal characteristics desired.

The beds of material utilized in the present invention may include beads, resins, granular materials, or compressed adsorbents

and may be charged or uncharged. Alternatively, in another embodiment, the filter may consist of stages in the form of sheets or webs of filtration media layered together through which the water is caused to flow. Each sheet may be constructed of a filtration media specifically designed for the removal of certain constituents. In still another embodiment, the filter may consist of stages in the form of concentric, cylindrical layers where water is caused to flow either radially inward or outward through the layers and then on to the point of use.

The scope of the present invention is not limited to any particular embodiment set forth herein. Instead, the present invention requires that, regardless of a particular embodiment, configuration, or shape of the device in which the filter is housed or used, the liquid is filtered prior to flow through the activated carbon using a filter media that removes microorganisms. As used herein with respect to action relative to microorganisms, "removal of microorganisms" includes the killing, capturing, or deactivation of such microorganisms.

In addition, without limiting the scope of the present invention, additional stages of filter media may be added to the filter, depending upon the constituents sought to be removed. These stages may be located before or after the stage which includes activated charcoal. Again, the present invention requires that at least one stage for the removal of microorganisms precedes the stage containing activated charcoal.

The entire filter apparatus, having at least two stages, may be assembled into a variety of physical shapes and configurations depending upon the intended consumer or application. For example, and without limiting the scope of the present invention, a device

containing the filter media may be readily attached to the spigot of a kitchen sink or other tap supplying water. In still another configuration, a device containing the filter unit that fits into a cabinet or within the plumbing of a residence or business may be utilized.

- 5 Other embodiments include the use of the apparatus in a pitcher, sports bottle, or other dispenser.

In one particular embodiment of the present invention, water entering the filter apparatus first passes through a stage constructed of a meltblown web, a charge-modified meltblown, a glass fiber web, or a charge-modified glass fiber web. This stage acts to remove turbidity-related components which may act to cloud the liquid and various sediments, as well as certain organic components. The water then passes through another stage constructed of a one or more microporous materials such as microfiber glass.

- 10
15 Microorganisms, including bacteria, are primarily removed by this stage.

Subsequent to these two stages, the water passes through a stage of activated carbon where other impurities are removed through adsorption. As the bacteria has already been removed prior to this stage, the activated carbon becomes less fouled with microorganisms such as bacteria.

- 20
These and other features, aspects and advantages of the present invention will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate an embodiment of the invention and, together with the description, serve to explain the principles of the invention.

Brief Description of the Drawings

A full and enabling disclosure of the present invention,

including the best mode thereof, to one of ordinary skill in the art, is set forth more particularly in the remainder of the specification, including reference to the accompanying drawings, in which:

FIG. 1 is a diagrammatic representation of an embodiment of the present invention showing water flow through the filter media.

FIG. 2 is a diagrammatic representation of another embodiment of the present invention showing water flow through the filter media.

FIG. 3 is a diagrammatic representation of a cylindrical embodiment of the filter stages for the present invention (without a chamber).

FIG. 4 is a diagrammatic representation of a cylindrical embodiment of the filter stages for the present invention (without a chamber).

Detailed Description of the Preferred Embodiments

Reference now will be made in detail to the embodiments of the invention, one or more examples of which are set forth below. Each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope or spirit of the invention. For instance, features illustrated or described as part of one embodiment, can be used on another embodiment to yield a still further embodiment. Thus, it is intended that the present invention cover such modifications and variations as come within the scope of the appended claims and their equivalents. Other objects, features and aspects of the present invention are disclosed in or are obvious from the following detailed description. It is to be understood by one of ordinary skill in the art that the present discussion is a description

of exemplary embodiments only, and is not intended as limiting the broader aspects of the present invention.

In general, the present invention relates to a method and apparatus for filtering a liquid that reduces bacteria contact with the activated charcoal stage of a fluid filter. More specifically, a filter stage may be placed in the water stream of a multistage filter at a point in flow prior to the activated carbon stage such that microorganisms are substantially removed from the water prior to the filtration by the activated carbon.

As shown in Fig. 1, a multistage water filter 10 includes a chamber 12 having an inlet 14 for water flow; an outlet 16 for water flow; a first filter stage 18 within chamber 12 and in fluid communication with inlet 14; and a second filter stage 20 within chamber 12 and in fluid communication with outlet 16. The second filter stage 20 is located within the chamber 12 at a position that allows water to pass through the first filter stage 18 prior to passing through the second filter stage 20, as demonstrated by the arrows of Fig. 1 that depict the direction of water flow.

It is to be understood that various other arrangements of the filter stages could be utilized. For example, the stages may not be present within the same chamber but may be in fluid communication through tubing or the like.

The first filter stage 18 is constructed of a filter media that removes, captures, kills, or deactivates microorganisms. Examples of materials that may be used for first filter stage 18 are microporous materials such as a nonwoven meltblown web, a nonwoven microfiber glass web or various charge-modified media such as a nonwoven charge-modified meltblown web or a nonwoven charge-modified microfiber glass web. Other filter media that may be utilized

for this first filter stage include media that kill or deactivate the microorganisms.

Generally, if microporous materials are employed, such materials may have pore sizes that are 20 microns or less in size, and in some embodiments, pore sizes that are 10 microns or less in size. In other embodiments, the microporous materials will have a maximum pore size of 7.5 microns. These includes various microfiber glass configurations as well as various nonwoven webs.

As used herein, the term "nonwoven web" means a web or fabric having a structure of individual fibers or threads which are interlaid, but not in an identifiable manner as in a knitted or woven fabric. Nonwoven webs generally may be prepared by methods which are well known to those having ordinary skill in the art. Examples of such processes include, by way of illustration only, meltblowing, coforming, spunbonding, carding and bonding, air laying, and wet laying. Meltblowing, coforming, and spunbonding processes are exemplified by the following references, each of which is incorporated herein by reference:

(a) meltblowing references include, by way of example, U.S. Patent Nos. 3,016,599 to R. W. Perry, Jr., 3,704,198 to J. S. Prentice, 3,755,527 to J. P. Keller et al., 3,849,241 to R. R. Butin et al., 3,978,185 to R. R. Butin et al., and 4,663,220 to T. J. Wisneski et al. See, also, V. A. Wentz, "Superfine Thermoplastic Fibers", Industrial and Engineering Chemistry, Vol. 48, No. 8, pp. 1342-1346 (1956); V. A. Wentz et al., "Manufacture of Superfine Organic Fibers", Navy Research Laboratory, Washington, D.C., NRL Report 4364 (111437), dated May 25, 1954, United States Department of Commerce, Office of Technical Services; and Robert R. Butin and Dwight T. Lohkamp, "Melt Blowing - A One-Step Web Process for

New Nonwoven Products", Journal of the Technical Association of the Pulp and Paper Industry, Vol. 56, No.4, pp. 74-77 (1973);

(b) coforming references include U.S. Patent Nos. 4,100,324 to R. A. Anderson et al. and 4,118,531 to E. R. Hauser; and

(c) spunbonding references include, among others, U.S. Patent Nos. 3,341,394 to Kinney, 3,655,862 to Dorschner et al., 3,692,618 to Dorschner et al., 3,705,068 to Dobo et al., 3,802,817 to Matsuki et al., 3,853,651 to Porte, 4,064,605 to Akiyama et al., 4,091,140 to Harmon, 4,100,319 to Schwartz, 4,340,563 to Appel and Morman, 4,405,297 to Appel and Morman, 4,434,204 to Hartman et al., 4,627,811 to Greiser and Wagner, and 4,644,045 to Fowells.

A nonwoven charge-modified microfiber glass web may be prepared from a fibrous web which incorporates glass fibers having a cationically charged coating thereon. Generally, such microfibers would be glass fibers having a diameter of about 10 microns or less. The coating includes a functionalized cationic polymer which has been crosslinked by heat; in other words, the functionalized cationic polymer has been crosslinked by heat after being coated onto the glass fibers. Such fibrous filter is prepared by a method which involves providing a fibrous filter which includes glass fibers, passing a solution of a functionalized cationic polymer crosslinkable by heat through the fibrous filter under conditions sufficient to substantially coat the fibers with the functionalized cationic polymer, and treating the resulting coated fibrous filter with heat at a temperature and for a time sufficient to crosslink the functionalized cationic polymer present on the glass fibers. The functionalized cationic polymer may be an epichlorohydrin-functionalized polyamine or an epichlorohydrin-functionalized polyamido-amine.

In general, when used as a filter media, a charge-modified microfiber glass web will contain at least about 50 percent by weight of glass fibers, based on the weight of all fibers present in the filter media. In some embodiments, essentially 100 percent of the fibers will be glass fibers. When other fibers are present, however, they generally will be cellulosic fibers, fibers prepared from synthetic thermoplastic polymers, or mixtures thereof.

As used herein, the terms "cationically charged" in reference to a coating on a glass fiber and "cationic" in reference to the functionalized polymer mean the presence in the respective coating and polymer of a plurality of positively charged groups. Thus, the terms "cationically charged" and "positively charged" are synonymous. Such positively charged groups typically will include a plurality of quaternary ammonium groups, but they are not necessarily limited thereto.

The term "functionalized" is used herein to mean the presence in the cationic polymer of a plurality of functional groups, other than the cationic groups, which are capable of crosslinking when subjected to heat. Thus, the functional groups are thermally crosslinkable groups. Examples of such functional groups include epoxy, ethylenimino, and episulfido. These functional groups readily react with other groups typically present in the cationic polymer. The other groups typically have at least one reactive hydrogen atom and are exemplified by amino, hydroxy, and thiol groups. It may be noted that the reaction of a functional group with another group often generates still other groups which are capable of reacting with functional groups. For example, the reaction of an epoxy group with an amino group results in the formation of a β -hydroxyamino group.

Thus, the term "functionalized cationic polymer" is meant to

include any polymer which contains a plurality of positively charged groups and a plurality of other functional groups which are capable of being crosslinked by the application of heat. Particularly useful examples of such polymers are epichlorohydrin-functionalized polyamines and epichlorohydrin-functionalized polyamido-amines. Both types of polymers are exemplified by the Kymene[®] resins which are available from Hercules Inc., Wilmington, Delaware. Other suitable materials include cationically modified starches, such as such as RediBond, from National Starch.

As used herein, the term "thermally crosslinked" means the coating of the functionalized cationic polymer has been heated at a temperature and for a time sufficient to crosslink the above-noted functional groups. Heating temperatures typically may vary from about 50°C to about 150°C. Heating times in general are a function of temperature and the type of functional groups present in the cationic polymer. For example, heating times may vary from less than a minute to about 60 minutes or more.

A nonwoven charge-modified meltblown web may consist of hydrophobic polymer fibers, amphiphilic macromolecules adsorbed onto at least a portion of the surfaces of the hydrophobic polymer fibers, and a crosslinkable, functionalized cationic polymer associated with at least a portion of the amphiphilic macromolecules, in which the functionalized cationic polymer has been crosslinked. Crosslinking may be achieved through the use of a chemical crosslinking agent or by the application of heat. Desirably, thermal crosslinking, i.e., the application of heat, will be employed. In general, the amphiphilic macromolecules may be of one or more of the following types: proteins, poly(vinyl alcohol), monosaccharides, disaccharides, polysaccharides, polyhydroxy compounds,

polyamines, polylactones, and the like. Desirably, the amphiphilic macromolecules will be amphiphilic protein macromolecules, such as globular protein or random coil protein macromolecules. For example, the amphiphilic protein macromolecules may be milk protein macromolecules. The functionalized cationic polymer typically may be any polymer which contains a plurality of positively charged groups and a plurality of other functional groups which are capable of being crosslinked by, for example, chemical crosslinking agents or the application of heat. Particularly useful examples of such polymers are epichlorohydrin-functionalized polyamines and epichlorohydrin-functionalized polyamido-amines. Other suitable materials include cationically modified starches.

The nonwoven charge-modified meltblown web may be prepared by a method which involves providing a fibrous meltblown filter media which includes hydrophobic polymer fibers, passing a solution containing amphiphilic macromolecules through the fibrous filter under shear stress conditions so that at least a portion of the amphiphilic macromolecules are adsorbed onto at least some of the hydrophobic polymer fibers to give an amphiphilic macromolecule-coated fibrous web, passing a solution of a crosslinkable, functionalized cationic polymer through the amphiphilic macromolecule-coated fibrous web under conditions sufficient to incorporate the functionalized cationic polymer onto at least a portion of the amphiphilic macromolecules to give a functionalized cationic polymer-coated fibrous web in which the functionalized cationic polymer is associated with at least a portion of the amphiphilic macromolecules, and treating the resulting coated fibrous filter with a chemical crosslinking agent or heat. Desirably, the coated fibrous filter will be treated with heat at a temperature and for a time

sufficient to crosslink the functionalized cationic polymer.

5 The second filter stage 20 includes activated carbon. This may be present in granular form, or compressed into a volume having any of a myriad of shapes, including cylinders, sheets, and discs. Solid porous filter shapes are especially desirable for ease of handling and ready disposability. These may be manufactured by extruding a mixture of a thermoplastic binder material and a powdered or granular form of activated carbon. Various other components may be present in this activated carbon-containing stage, such as zeolites, ion-exchange resins, binder agents, and various other adsorbents.

10 As used herein, the term "thermoplastic binder" means any binder, typically a polymer, which is thermoplastic, i.e., capable of softening and flowing when heated and of hardening again when cooled. Examples of thermoplastic binders include, by way of illustration only, end-capped polyacetals, such as poly(oxymethylene) or polyform-aldehyde, poly(trichloroacetaldehyde), poly(n-valeraldehyde), poly(acetaldehyde), and poly(propionaldehyde); acrylic polymers, such as polyacrylamide, poly(acrylic acid),
15 poly(methacrylic acid), poly(ethyl acrylate), and poly(methyl methacrylate); fluorocarbon polymers, such as poly(tetrafluoroethylene), perfluorinated ethylene-propylene copolymers, ethylene-tetrafluoroethylene copolymers, poly(chlorotrifluoroethylene), ethylene-chlorotrifluoroethylene copolymers, poly(vinylidene fluoride), and
20 poly(vinyl fluoride); polyamides, such as poly(6-aminocaproic acid) or poly(e-caprolactam), poly(hexamethylene adipamide), poly(hexamethylene sebacamide), and poly(11-aminoundecanoic acid); polyaramides, such as poly(imino-1,3-phenyleneiminoisophthaloyl) or poly(m-phenylene isophthalamide); parylenes,

such as poly-*p*-xylylene, and poly(chloro-*p*-xylylene); polyaryl ethers, such as poly(oxy-2,6-dimethyl-1,4-phenylene) or poly(*p*-phenylene oxide); polyaryl sulfones, such as poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-1,4-phenyleneisopropylidene-1,4-phenylene), and
5 poly(sulfonyl-1,4-phenylene-oxy-1,4-phenylenesulfonyl-4,4'-biphenylene); polycarbonates, such as poly(bisphenol A) or poly(carbonyldioxy-1,4-phenyleneisopropylidene-1,4-phenylene); polyesters, such as poly(ethylene terephthalate), poly(tetramethylene terephthalate), and poly(cyclohexyl-ene-1,4-dimethylene terephthal-
10 ate) or poly(oxymethylene-1,4-cyclohexylenemethyleneoxytere-phthaloyl); polyaryl sulfides, such as poly(*p*-phenylene sulfide) or poly(thio-1,4-phenylene); polyimides, such as poly(pyromellitimido-1,4-phenylene); polyolefins, such as polyethylene, polypropylene, poly(1-butene), poly(2-butene), poly(1-pentene), poly(2-pentene),
15 poly(3-methyl-1-pentene), and poly(4-methyl-1-pentene); vinyl polymers, such as poly(vinyl acetate), poly(vinylidene chloride), and poly(vinyl chloride); diene polymers, such as 1,2-poly-1,3-butadiene, 1,4-poly-1,3-butadiene, polyisoprene, and polychloroprene; polystyrenes; and copolymers of the foregoing, such as acrylonitrile-
20 butadiene-styrene (ABS) copolymers.

The chamber 12 can be formed into any shape that accepts the filter structure and allows water to flow through the stages in the disclosed order. By way of example, the chamber 12 may be shaped for various point-of-use applications such as connection to a faucet
25 or insertion into the top of a pitcher. In such applications, the chamber (and thus the filter stages) are usually cylindrical. However, the present invention does not require only cylindrically-shaped chambers and filters.

Similarly, Figures 2, 3, and 4, each depict the elements found

in Fig. 1 but show different embodiments of the present invention.

These embodiments serve only as examples as multiple other embodiments may be readily envisioned by one skilled in the art based on the teachings set forth herein. For example, various

5 charge-modified media may be used as the filter stages prior to the stage that includes the activated carbon as well as after the activated carbon layer stage. For further example, a multistage filter may have a layer of charge-modified media as the first filter stage, then an activated charcoal-containing layer as the second filter stage,
10 followed by another layer of charge-modified media as a third filter stage which acts as a polishing stage to remove various unwanted contaminants after flow through the activated carbon-containing stage. In addition, multiple similar layers of the filter stages may be employed, such as a layer of charge-modified media, followed by an
15 activated carbon-containing layer, followed by two layers of charge-modified media, followed by another layer containing activated carbon, and then finally followed by a final layer of charge-modified media.

Fig. 2 represents a multistage water filter 110 having a
20 chamber 112 having an inlet 114 for water flow; an outlet 116 for water flow; a first filter stage 118 within chamber 112 and in fluid communication with inlet 114; a second filter stage 120 within chamber 112 and in fluid communication with outlet 116; and a third
25 filter stage 122 including a microporous material. The second filter stage 120 is located within the chamber 112 at a position that allows water to pass through the first filter stage 118 prior to passing through the second filter stage 120, as demonstrated by the arrows of Fig. 2 that depict the direction of water flow.

The third filter stage 122 is located within chamber 112 in a

position that allows water to pass through third filter stage 122 prior to passing through the second filter stage 120. Therefore, the third filter stage 122 may be located in a position that allows water to pass through third filter stage 122 after passing through the first filter stage 118 as demonstrated in Fig. 2, or the third filter stage 122 may be located in a position that allows water to pass through third filter stage 122 first, through first filter stage 118 second, and then through second filter stage 120. The second filter stage 120 includes activated carbon as discussed above with Fig. 1. The first filter stage 118 and third filter stage 122 may be constructed of microporous materials as described above with Fig. 1. In some embodiments, this third filter stage 122 may include a porous material that exhibits a gradient pore structure, meaning that the diameter of the pores vary from one surface of the filter stage to the other surface of the filter stage. For example, when the third filter stage is intended to act as a sediment-removal stage, the diameter of the pores may decrease from the initial fluid-contact surface to the fluid-outflow surface.

Fig. 3 is another embodiment of the present invention, shown with water flow moving radially inward, and then out of the cylinder in flow moving along the cylinder's hollow center axis. As depicted, the multistage water filter 210 includes an inlet 214 for water flow that is the outer face of the cylinder; an outlet 216 for water flow along the cylinder's hollow center axis; a first filter stage 218 in fluid communication with inlet 214; and a second filter stage 220 in fluid communication with outlet 216. The second filter stage 220 is located at a position that allows water to pass through the first filter stage 218 prior to passing through the second filter stage 220, as demonstrated by the arrows of Fig. 1 that depict the direction of water flow. A chamber, not depicted in Fig. 3, can readily be formed

to accept this embodiment by one skilled in the art. As with the
embodiments of Fig. 1 and Fig. 2, the first filter stage 218 includes a
filter media that removes microorganisms such as a charge-modified
meltblown or microfiber glass web. Similarly, the second filter stage
220 includes activated carbon. While not shown, a third filter stage
can readily be added to the embodiment of Fig. 3 through the
addition of a third, concentric layer of filter media. This third filter
stage may be added as a concentric layer to the outside of first filter
stage 218 or may be added as a concentric layer between first filter
stage 218 and second filter stage 220.

Fig. 4 is an embodiment with flow moving in a direction
opposite to what is described in Fig. 3. Specifically, water in Fig. 4
enters the device along the hollow center axis of the cylinder and
then moves radially outward through the filter stages. The multistage
water filter 310 of Fig. 4 includes an inlet 314 for water flow along the
cylinder's hollow center axis; an outlet 316 for water flow that is the
face of the cylinder; a first filter stage 318 in fluid communication with
inlet 314; and a second filter stage 320 in fluid communication with
outlet 316. The second filter stage 320 is located at a position that
allows water to pass through the first filter stage 318 prior to passing
through the second filter stage 320, as demonstrated by the arrows
of Fig. 1 that depict the direction of water flow. A chamber, not
depicted in Fig. 3, can readily be formed to accept this embodiment
by one skilled in the art. As with the embodiments of Fig. 1, Fig. 2,
and Fig. 3, the first filter stage 318 includes a filter media that
removes microorganisms. Similarly, the second filter stage 320
includes activated carbon. While not shown, a third filter stage can
readily be added to the embodiment of Fig. 4 through the addition of
a third, concentric layer of filter media. This third filter stage may be

added as a concentric layer to the inside of first filter stage 318 or may be added as a concentric layer between first filter stage 318 and second filter stage 320.

Referring now to Fig. 2, to obtain filtered water, chamber 110 is connected within the path of water flow. Water passes through first filter stage 118 where microorganisms are removed from the water. Water then passes through third filter stage 122 where sediment and some organics are removed from the water. Flowing into the second filter stage 120, the activated carbon removes certain heavy metals, chlorine, and residual sediment from the water. Water then exits the second filter stage 120, passes through the outlet for water flow 116, out of chamber 110, and on to consumption or filtered water storage. Similarly, the arrows of Fig. 1, Fig. 3, and Fig. 4 depict the direction of water flow through these respective embodiments with each filter stage performing as described with Fig. 2.

Although preferred embodiments of the invention have been described using specific terms, devices, and methods, such description is for illustrative purposes only. The words used are words of description rather than of limitation. It is to be understood that changes and variations may be made by those of ordinary skill in the art without departing from the spirit or the scope of the present invention, which is set forth in the following claims. In addition, it should be understood that aspects of the various embodiments may be interchanged both in whole or in part. Therefore, the spirit and scope of the appended claims should not be limited to the description of the preferred versions contained therein.

What is claimed is:

1. A multistage liquid filter, comprising:
a chamber having an inlet for liquid flow and an outlet for liquid flow;
5 a first filter stage within said chamber in fluid communication with said inlet, said first filter stage comprising a material that removes microorganisms;
a second filter stage within said chamber in fluid communication with said outlet, said second filter stage comprising
10 activated carbon; and
said second filter stage being located within said chamber at a position that allows liquid to pass through said first filter stage prior to passing through said second filter stage.
2. A multistage liquid filter as recited in claim 1, further
15 comprising a third filter stage within said chamber, said third filter stage being constructed of a microporous material, said third filter stage being located within said chamber at a position that allows liquid to pass through said third filter stage prior to passing through said second filter stage.
- 20 3. A multistage liquid filter as recited in claim 1, wherein said liquid is water.
4. A multistage liquid filter as recited in claim 2, wherein said third filter stage is located within said chamber at a position that allows liquid to pass through said third filter stage after passing
25 through said first filter stage.
5. A multistage liquid filter as recited in claim 2, wherein said third filter stage comprises microfiber glass.
6. A multistage liquid filter as recited in claim 5, wherein said microfiber glass is charge-modified.
- 30 7. A multistage filter as recited in claim 6, wherein said filter

is connected at the point of use for a water supply.

8. A multistage liquid filter as recited in claim 2, wherein said third filter stage comprises a meltblown web.

5 9. A multistage liquid filter as recited in claim 2, wherein said third filter stage comprises a material that selectively removes turbidity-related components, sediment, and some organic materials.

10. A multistage filter as recited in claim 2, wherein said filter is connected at the point of use for a water supply.

11. A multistage liquid filter as recited in claim 1, wherein said first filter stage comprises a meltblown web.

12. A multistage liquid filter as recited in claim 1, wherein said first filter stage comprises microfiber glass.

13. A multistage liquid filter as recited in claim 12, wherein said microfiber glass is charge-modified.

15 14. A multistage filter as recited in claim 13, wherein said filter is connected at the point of use for a water supply.

15. A multistage filter as recited in claim 1, wherein said first filter stage is a microporous material.

20 16. A multistage filter as recited in claim 2, wherein said third filter stage consists of a bed of granular material.

17. A multistage filter as recited in claim 1, wherein said filter is connected at the point of use for a water supply.

18. A multistage process for filtering impurities from a liquid, said process comprising the steps of:

25 supplying liquid to a filter;

removing at least a portion of the microorganisms from said liquid supply in a first filtering step; and

then removing at least a portion of the organics and other non-biological components in a second filtering step using activated

carbon.

19. A multistage liquid filtration process as recited in claim 18, wherein said first filtering step is accomplished using a meltblown web.

5 20. A multistage liquid filtration process as recited in claim 18, wherein said first filtering step is accomplished using a microfiber glass web.

21. A multistage liquid filtration process as recited in claim 18, wherein said first filtering step is accomplished using a charge-modified microfiber glass web.

22. A multistage process for liquid filtration as recited in claim 21, wherein said filtering steps are conducted at the point of use for a water supply.

23. A multistage process for liquid filtration as recited in claim 18, wherein said filtering steps are conducted at the point of use for a water supply.

24. A multistage liquid filtration process as recited in claim 18 further comprising a third filtering step that removes sediments and some organics prior in flow to said second filtering step.

20 25. A multistage process for liquid filtration as recited in claim 24, wherein said filtering steps are conducted at the point of use for a water supply.

26. A multistage liquid filtration process as recited in claim 24, wherein said third filtering step is accomplished using a microfiber glass web.

27. A multistage liquid filtration process as recited in claim 24 wherein said third filtering step occurs before said first filtering step.

28. A multistage liquid filtration process as recited in claim 27 wherein said third filtering step occurs after said first filtering step.

29. A multistage liquid filtration process as recited in claim 18 wherein said liquid is water.

30. A multistage liquid filter, comprising:

an inlet for liquid flow and an outlet for liquid flow;

5 a first filter stage in fluid communication with said inlet, said first filter stage comprising a material that removes microorganisms;

a second filter stage in fluid communication with said outlet, said second filter stage comprising activated carbon; and

10 said second filter stage being located at a position that allows liquid to pass through said first filter stage prior to passing through said second filter stage.

31. A multistage filter as recited in claim 30, wherein said filter is connected at the point of use for a water supply.

15 32. A multistage filter as recited in claim 30, wherein said first filter stage is a microporous material.

33. A multistage liquid filter as recited in claim 30, wherein said first filter stage comprises a meltblown web.

34. A multistage liquid filter as recited in claim 30, wherein said first filter stage comprises microfiber glass.

20 35. A multistage liquid filter as recited in claim 34, wherein said microfiber glass is charge-modified.

36. A multistage filter as recited in 35, wherein said filter is connected at the point of use for a water supply.

25 37. A multistage liquid filter as recited in claim 30, further comprising a third filter stage, said third filter stage being constructed of a microporous material, said third filter stage being located at a position that allows liquid to pass through said third filter stage prior to passing through said second filter stage.

38. A multistage liquid filter as recited in claim 37, wherein

said third filter stage is located at a position that allows liquid to pass through said third filter stage after passing through said first filter stage.

39. A multistage liquid filter as recited in claim 37, wherein
5 said third filter stage comprises a meltblown web.

40. A multistage liquid filter as recited in claim 37, wherein
said third filter stage comprises microfiber glass.

41. A multistage liquid filter as recited in claim 40, wherein
10 said microfiber glass is charge-modified.

42. A multistage filter as recited in claim 41, wherein said
filter is connected at the point of use for a water supply.

43. A multistage liquid filter as recited in claim 37, wherein
15 said third filter stage comprises a material that selectively removes
turbidity-related components, sediment, and some organic materials.

44. A multistage liquid filter as recited in claim 37, wherein
said third filter stage consists of a bed of granular material.

45. A multistage liquid filter as recited in claim 37, wherein
said filter is connected at the point of use for a water supply.

46. A multistage liquid filter as recited in claim 37, wherein
20 said liquid is water.

47. A multistage liquid filter as recited in claim 30, wherein
said liquid is water.

Abstract of the Disclosure

- 5 The present invention provides a multistage liquid filtering apparatus and a multistage process for filtering microorganisms and other unwanted impurities from the liquid. The invention employs a microorganism-removing filter stage prior to an activated carbon filter stage and especially adaptable for use with home water supplies.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204